

# BULKSPREAD



## Features

- **High-Quality Painted Mild Steel Bin and Chassis Construction** is a welded construction made of sheet metal and plate. The chassis is constructed of high-grade tubing to offer additional strength and flex.
- **Hitch Safety Chain** in case the hitch, hitch bolts or tractor drawbar break.
- **A Robust Parking Jack** for easy hitching and detachment of the machine.
- **S-design Drawbar** for a sharper turning circle ensuring greater, more streamlined movability.

## Pick Your Extras

- **3CR12 Bin Construction**
- **304 Stainless Steel Bin Construction**
- **Stand-alone hydraulic power-pack**
- **Rear Belt Attachment**
- **Integrated Steel Grid**
- **Single Channel ISO Bus Kit**
- **Dual Channel ISO Bus Kit**
- **Camera Package**
- **Flood Light Package**
- **Road Light Package**
- **Tarpaulin Kit**
- **Weighing System Kit**

## Specifications

MODEL	RSP100-11.0G	RSP100-11.0H	RSP100-13.0G	RSP100-13.0H
<b>LOAD CAPACITY (kg/lbs)</b>	11000 (24251)	11000 (24251)	13000 (28660)	13000 (28660)
<b>CAPACITY (m<sup>3</sup>/ft<sup>3</sup>)</b>	8 (283)	8 (283)	10 (353)	10 (353)
<b>EMPTY WEIGHT (kg/lbs)</b>	2600 (5732)	2600 (5732)	2850 (6283)	2850 (6283)
<b>REQ. OIL FLOW (l/min/gal/min)</b>	50 (13.2)	110 (29)	50 (13.2)	110 (29)
<b>3 SPEED GROUND RELATED GEARBOX</b>	•	•	•	•
<b>HYDRAULIC DRIVE GEARBOX</b>	•	22:01	•	22:01
<b>AXLE (mm/inch)</b>	90 (3-1/2)	90 (3-1/2)	100 (3-15/16)	100 (3-15/16)
<b>WHEELS</b>	2 x 560/60 R 22.5	2 x 560/60 R 22.5	2 x 600/55 R 26.5	2 x 600/55 R 26.5
<b>TRACTOR POWER REQUIREMENT (kw/hp)</b>	105 (140)	105 (140)	135 (180)	135 (180)
<b>A - OVERALL LENGTH (mm/inch)</b>	6490 (255-1/2)	6490 (255-1/2)	7011 (276)	7011 (276)
<b>B - DRAWBAR LENGTH (mm/inch)</b>	1948 (76-11/16)	1948 (76-11/16)	1948 (76-11/16)	1948 (76-11/16)
<b>C - BIN LENGTH (mm/inch)</b>	3606 (141-15/16)	3606 (141-15/16)	4206 (165-9/16)	4206 (165-9/16)
<b>D - REAR SECTION LENGTH (mm/inch)</b>	932 (36-11/16)	932 (36-11/16)	932 (36-11/16)	932 (36-11/16)
<b>E - OVERALL WIDTH (mm/inch)</b>	2510 (98-7/8)	2510 (98-7/8)	2660 (104-3/4)	2660 (104-3/4)
<b>F - BIN WIDTH (mm/inch)</b>	2200 (86-5/8)	2200 (86-5/8)	2200 (86-5/8)	2200 (86-5/8)
<b>G - WHEEL CENTRES (mm/inch)</b>	1950 (76-3/4)	1950 (76-3/4)	2050 (80-3/4)	2050 (80-3/4)
<b>H - OVERALL HEIGHT (mm/inch)</b>	2493 (98-3/16)	2493 (98-3/16)	2559 (100-3/4)	2559 (100-3/4)
<b>I - HITCH HEIGHT (mm/inch)</b>	496±50 (19-1/2±2)	496±50 (19-1/2±2)	528±50 (20-3/4±2)	528±50 (20-3/4±2)
<b>J - AXLE HEIGHT (mm/inch)</b>	621 (24-7/16)	621 (24-7/16)	622 (24-7/16)	622 (24-7/16)

• = Not Applicable    ● = Standard