

COMPACSPREAD



Features

- **High-Quality Painted Mild Steel Bin and Chassis Construction** is a welded construction made of sheet metal and plate. The chassis is constructed of high-grade tubing to offer additional strength and flex.
- **Hitch Safety Chain** in case the hitch, hitch bolts or tractor drawbar break.
- **A Robust Parking Jack** for easy hitching and detachment of the machine.
- **S-design Drawbar** for a sharper turning circle ensuring greater, more streamlined movability.
- **Integrated Steel Grid** can remove foreign objects 65mm in diameter and bigger.
- **Orchard/Vineyard Spreading Kit** to deflect material underneath trees and vines without distributing material directly behind the machine.

Pick Your Extras

- **3CR12 Bin Construction**
- **304 Stainless Steel Bin Construction**
- **Stand-alone hydraulic power pack**
- **Rear Belt Attachment**
- **PTO Power Pack**
- **Integrated Grid**
- **Single Channel ISO Bus Kit**
- **Dual Channel ISO Bus Kit**
- **Camera Package**
- **Flood Light Package**
- **Road Light Package**
- **Tarpaulin Kit**
- **Weighing System Kit**

Specifications

MODEL	RSP050-2.5G	RSP050-2.5H	RSP073-5.0G	RSP073-5.0H
LOAD CAPACITY (kg/lbs)	3000 (6614)	3000 (6614)	5000 (11023)	5000 (11023)
CAPACITY (m ³ /ft ³)	2.5 (88)	2.5 (88)	4.5 (159)	4.5 (159)
REQ. OIL FLOW (l/min/gal/min)	50 (13.2)	110 (29)	50 (13.2)	110 (29)
EMPTY WEIGHT (kg/lbs)	950 (2094)	950 (2094)	1450 (3197)	1450 (3197)
3 SPEED GROUND RELATED GEARBOX	•	•	•	•
HYDRAULIC DRIVE GEARBOX	•	16:01	•	22:01
AXLE (mm/inch)	60 (2-3/8)	60 (2-3/8)	70 (2-3/4)	7 (2-3/4)
WHEELS	2 x 12.5/80-15.3	2 x 12.5/80-15.3	2 x 12.5/80-18.0	2 x 12.5/80-18.0
TRACTOR POWER REQUIREMENT (kw/hp)	45 (60)	46 (60)	56 (75)	56 (75)
A - OVERALL LENGTH (mm/inch)	4600 (181-1/8)	4600 (181-1/8)	6000 (236-1/4)	6000 (236-1/4)
B - DRAWBAR LENGTH (mm/inch)	1541 (60-11/16)	1541 (60-11/16)	1541 (60-11/16)	1541 (60-11/16)
C - BIN LENGTH (mm/inch)	2400 (94-1/2)	2400 (94-1/2)	360 (141-3/4)	3600 (141-3/4)
D - REAR SECTION LENGTH (mm/inch)	800 (31-1/2)	800 (31-1/2)	800 (31-1/2)	800 (31-1/2)
E - OVERALL WIDTH (mm/inch)	1500 (59-1/16)	1500 (59-1/16)	1958 (77-1/16)	1958 (77-1/16)
F - BIN WIDTH (mm/inch)	1300 (51-3/16)	1300 (51-3/16)	1300 (51-3/16)	1300 (51-3/16)
G - WHEEL CENTRES (mm/inch)	1350 (53-3/16)	1350 (53-3/16)	1650 (64-15/16)	1650 (64-15/16)
H - OVERALL HEIGHT (mm/inch)	1400 (55-1/8)	1400 (55-1/8)	1850 (72-7/8)	1850 (72-7/8)
I - HITCH HEIGHT (mm/inch)	430 (16-15/16)	430 (16-15/16)	430 (16-15/16)	430 (16-15/16)
J - AXLE HEIGHT (mm/inch)	430 (16-15/16)	430 (16-15/16)	430 (16-15/16)	430 (16-15/16)

• = Not Applicable ● = Standard