

# ECONOSPREAD



## Features

- **High-Quality Painted Mild Steel Bin and Chassis Construction** is a welded construction made of sheet metal and plate. The chassis is constructed of high-grade tubing to offer additional strength and flex.
- **Hitch Safety Chain** in case the hitch, hitch bolts or tractor drawbar break.
- **A Robust Parking Jack** for easy hitching and detachment of the machine.
- **S-design Drawbar** for a sharper turning circle ensuring greater, more streamlined movability.

## Pick Your Extras

- **Integrated Steel Grid**
- **3CR12 Bin Construction**
- **304 Stainless steel bin construction**
- **Stand-alone hydraulic power-pack**
- **Rear Belt Attachment**
- **Orchard/Vineyard Spreading Kit**
- **Single Channel ISO Bus Kit**
- **Camera Package**
- **Flood Light Package**
- **Road Light Package**
- **Tarpaulin Kit**
- **Weighing System Kit**

## Specifications

MODEL	RSP050-5.OG	RSP050-5.OH	RSP050-7.OG	RSP050-7.OGTD	RSP050-7.OH	RSP050-7.OHTD
<b>LOAD CAPACITY (kg/lbs)</b>	5000 (11023)	5000 (11023)	7000 (15432)	7000 (15432)	7000 (15432)	7000 (15432)
<b>CAPACITY (m<sup>3</sup>/ft<sup>3</sup>)</b>	4 (141.3)	4 (141.3)	6 (211.9)	6 (211.9)	6 (211.9)	6 (211.9)
<b>EMPTY WEIGHT (kg/lbs)</b>	1450 (3196.7)	1450 (3196.7)	1600 (3527.4)	1600 (3527.4)	1600 (3527.4)	1600 (3527.4)
<b>REQ. OIL FLOW (l/min/gal/min)</b>	50 (13.2)	110 (29)	50 (13.2)	50 (13.2)	110 (29)	110 (29)
<b>3 SPEED GROUND RELATED GEARBOX</b>	•	•	•	•	•	•
<b>HYDRAULIC DRIVE GEARBOX</b>	•	16:01	•	•	16:01	16:01
<b>AXLE (mm/inch)</b>	70 (2-3/4)	70 (2-3/4)	80 (3-1/8)	80 (3-1/8)	80 (3-1/8)	80 (3-1/8)
<b>WHEELS</b>	2 x 500/50 R 22.5	2 x 500/50 R 22.5	2 x 500/60 R 22.5	2 X 480/80 R 30	2 x 500/60 R 22.5	2 X 480/80 R 30
<b>TRACTOR POWER REQ. (kw/hp)</b>	56 (75)	56 (75)	71 (95)	71 (95)	71 (95)	71 (95)
<b>A - OVERALL LENGTH (mm/inch)</b>	5349 (210-9/16)	5349 (210-9/16)	5326 (209-11/16)	5326 (209-11/16)	5326 (209-11/16)	5326 (209-11/16)
<b>B - DRAWBAR LENGTH (mm/inch)</b>	1541 (60-11/16)	1541 (60-11/16)	1541 (60-11/16)	1541 (60-11/16)	1541 (60-11/16)	1541 (60-11/16)
<b>C - BIN LENGTH (mm/inch)</b>	3006 (118-3/8)	3006 (118-3/8)	3006 (118-3/8)	3006 (118-3/8)	3006 (118-3/8)	3006 (118-3/8)
<b>D - REAR SECTION LENGTH (mm/inch)</b>	779 (30-11/16)	779 (30-11/16)	779 (30-11/16)	779 (30-11/16)	779 (30-11/16)	779 (30-11/16)
<b>E - OVERALL WIDTH (mm/inch)</b>	2210 (87)	2210 (87)	2310 (90-15/16)	2189 (86-3/16)	2310 (90-15/16)	2189 (86-3/16)
<b>F - BIN WIDTH (mm/inch)</b>	1846 (72-11/16)	1846 (72-11/16)	2130 (83-7/8)	2130 (83-7/8)	2130 (83-7/8)	2130 (83-7/8)
<b>G - WHEEL CENTRES (mm/inch)</b>	1800 (70-7/8)	1800 (70-7/8)	1800 (70-7/8)	1800 (70-7/8)	1800 (70-7/8)	1800 (70-7/8)
<b>H - OVERALL HEIGHT (mm/inch)</b>	2027 (79-13/16)	2027 (79-13/16)	2361 (92-15/16)	2256 (88-13/16)	2361 (92-15/16)	2256 (88-13/16)
<b>I - HITCH HEIGHT (mm/inch)</b>	453±50 (17-13/16±2)	453±50 (17-13/16±2)	522±50 (20-9/16±2)	482±50 (18-15/16±2)	522±50 (20-9/16±2)	482±50 (18-15/16±2)
<b>J - AXLE HEIGHT (mm/inch)</b>	539 (21-1/4)	539 (21-1/4)	585 (23-1/16)	695 (27-3/8)	585 (23-1/16)	695 (27-3/8)

• = Not Applicable    • = Standard